



Scan QR Code for installation
and operation manual



96" SUMMIT OPEN LINEAR LUXURY FIREPLACE

UNIT DIMENSIONS


Front Width: 102"

Height: 52 $\frac{3}{4}$ "


Depth: 22"

BTUs: SML-96BR-VEN (NG): 80,000 - 120,000
SML-96BR-VEP (LP): 60,000 - 120,000


FRONT PHYSICAL DIMENSIONS




TOP VIEW




SIDE ELEVATION



FRONT ELEVATION



REAR ELEVATION



FIREPLACE BURNER OPTIONS

BEDROCK CONTEMPORARY



Must add 1/2" reflective glass or lava granules (5 lbs/foot)

— Optional

6" Cannonballs in black, gray, or white

72" Western Driftwood Linear Log Set, 13 pieces


BEDROCK TRADITIONAL WITH GLOWFIRE™ LOGS




Must add 1/2" reflective glass or lava granules (5 lbs/foot)

Driftwood GlowFire™ logs included.

FIREPLACE PANELS



3/8" TEMPERED
BLACK GLASS




BLACK MATTE



BLACK FLUTED FIBER



OFFSET BLACK
FIBER BRICK



STACKED GRAY
FIBER BRICK

VIEWING REDUCTION KIT

Viewing reduction kits are available as an add-on to reduce the viewing area by 6" in height, from 24" to 18" high. The kit included the firebox reduction panel and side drywall stops.


*If installing as a corner view or bay corner(s), reduction kits are required.

OPTIONAL POWER VENT KIT

Power vent kits are available as an add-on to provide greater flexibility in fireplace placement and vent routing, while ensuring safe and efficient operation.

FRONT VIEW


FRAMING DIMENSIONS



Width: 102 $\frac{3}{8}$ " | **Height:** 53" | **Depth:** 22" | **Weight:** 530 lbs


Bottom to Drywall Stop: 6 $\frac{3}{4}$ "

Viewing Area: 98 $\frac{1}{2}$ "



BAY VIEW


FRAMING DIMENSIONS



Width: 100 $\frac{5}{8}$ " | **Height:** 53" | **Depth:** 22" | **Weight:** 530 lbs


Bottom to Drywall Stop: 6 $\frac{3}{4}$ "

Viewing Area: 99 $\frac{5}{8}$ "



LEFT VIEW

FRAMING DIMENSIONS




Reverse for right view

Width: 101 $\frac{5}{8}$ " | **Height:** 53" | **Depth:** 22" | **Weight:** 530 lbs


Bottom to Drywall Stop: 6 $\frac{3}{4}$ "

Viewing Area: 99"




CORNER VIEW

FRAMING DIMENSIONS



Width: 102 $\frac{3}{8}$ " | **Height:** 53" | **Wall to Wall:** 102 $\frac{3}{4}$ " | **Weight:** 530 lbs

Bottom to Drywall Stop: 6 $\frac{3}{4}$ " | **Viewing Area:** 95 $\frac{1}{4}$ " | **Angle:** 85 $\frac{1}{8}$ "



MINIMUM CLEARANCE TO COMBUSTIBLES

Back and sides of fireplaces	0" minimum
Floor	0" minimum
Perpendicular wall to opening	19" minimum
Top of fireplace	0" or top of studs minimum
Chimney outer pipe surface	1" minimum

VENTING


12" B-Vent
 *Minimum Height 14"
 *No more than two 45° offsets

**Unless using power vent*

MANTEL CLEARANCES

A combustible mantle shelf may be installed a maximum of 12" (22.9 cm) from the wall.

A combustible mantle shelf may be installed at a minimum of 6" above the opening of the fireplace and a maximum of 12" from the wall.



REQUIREMENTS FOR TV INSTALLATION

You can safely place a TV above the Summit fireplace, but the required clearance will depend on the TV manufacturer's guidelines.

When installing a TV 18" above the opening of the fireplace a mantel for heat deflection is required. If installing a TV 18" or more above the opening please refer to the TV manufacturer's required clearances guideline.



MAKEUP-AIR REQUIREMENTS

SUMMIT SIZE	CONFIGURATION	CFM
96"	Front View	832
96"	Corner View	1004
96"	Bay View	1185

The product information provided is not complete and is subject to change without notice.

To avoid the risk of fire and potential injury, product installation must adhere strictly to instructions contained in the Installation and Operation Manual.